

The Science of Surface and Ground Water Subsurface Movement of Water

2.5.0 Introduction: hydrologic cycle, which is a continuous process of transformation of water in the form of water vapour as it evaporates from land and ocean, drifts away to clouds and condenses to fall as rain. Of the rain falling over the land surface, a part of it infiltrates into the soil and the balance flows down as surface runoff. From the point of view of water resources engineering, the surface water forms a direct source which is utilized for a variety of purposes. However, most of the water that infiltrates into the soil travels down to recharge the vast ground water stored at a depth within the earth. In fact, the ground water reserve is actually a huge source of fresh water and is many times that of surface water. water is present in the pores of soils and fissures of rock up to a depth beyond which there is solid rock with no gaps which can store water. Although water is present in the pores of the soil and permeable rocks, there is difference between that stored above the water table and below it. The soil above the water table has only part of the voids filled up with water mol

Some of the definitions related to subsurface water are as follows:

- o Soil water: The water stored in the upper layers of the soil from the ground surface up to the extent of roots of plants
- o Vadose water: That stored below in the region between soil water zone and the capillary fringe. It is a link between water infiltrating from the ground surface and moving down to the saturated layer of ground water
- o Capillary water: That which has risen from the saturated ground water region due to capillary action. Naturally, the pressure here would be less than atmospheric.
- o Ground water: This is the water in the fully saturated zone. Pressure of water here would be more than atmospheric.
- o Water table: An imaginary surface within ground below which all the voids of the soil or permeable rock are completely filled with water. Below this imaginary surface, the pore water pressure is atmospheric. As one moves downwards from the water table, the pressure increases according to the hydrostatic law. Above the water table, the voids of soil/porous rock are only partially saturated with water clinging to the surface of the solids by surface tension. Hence, the pressure here is sub-atmosphere.

2.5.2 Water pressure in unsaturated zone

the term 'ground water flow' is used generally to describe the flow of water in the saturated portion of soil or fractured bedrock. No doubt it is important from the point of extraction of water from the zone using wells, etc. But the unsaturated zone, too, is important because of the following reasons:

- o The water in the unsaturated zone is the source of moisture for vegetation (the soil water)
- o This zone is the link between the surface and subsurface hydrologic processes as rain water infiltrates through this zone to recharge the ground water.
- o Water evaporated or lost by transpiration from the unsaturated zone (mainly from the soil water zone) recharges the atmospheric moisture.

Further, the process of infiltration, quite important in hydrologic modeling catchment, is actually a phenomenon occurring in the unsaturated zone.

At the water table, the pressure head is zero (that is atmospheric), that in the unsaturated zone is positive. Movement of water in unsaturated zone

The negative pressure head in the unsaturated zone of the soil can be metaphorically expressed as the soil being "thirsty". All the pores of the soil here are not filled up. Hence, as soon as water is applied to the soil surface, it is "lapped up" by the soil matrix. Only if the water is applied in excess of the amount that it can "drink", would water flow over the land surface as surface runoff. This capacity of the soil in the unsaturated portion to absorb water actually depends on the volumetric water content, θ expressed as:

$$\frac{V_w}{V}$$

Where V_w is the volume of water and V is the unit volume of soil or rock.

What happens to the water that got absorbed (that is infiltrated) at the surface of the unsaturated soil during application of water from above? It moves downward due to gravity through inter connected pores that are filled with water. With increasing water content, more pores fill, and the rate of downward movement of water increases.

A measure of the average rate of movement of water within soil (or permeable bed rock) is the hydraulic conductivity, indicated as 'K', and has the unit of velocity. Though it is more or less constant for a particular type of soil in the saturated zone, it is actually a function of the moisture content in the unsaturated portion of the soil. As θ increases, so does K, and to be precise, it should correctly be written as $K(\theta)$, indicating K to be a function of θ . Figure 5 shows such a typical relation for an unsaturated soil.

Version 2 CE HT, Kharagpur

oo

-5
2><'1 U

U 0.1 0.2 0.3
Water Content (8)

FIGURE 5. Variation of Hydraulic Conductivity (K) with Water Content (3)

Actually, the moisture potential (ψ) is also a function of θ , as shown in Figure 6.

FIGURE 6. Variation of Moisture Potential and Water Content

Version 2 CE HT, Kharagpur

The relationship of unsaturated hydraulic conductivity and volumetric water content is determined experimentally. A sample of soil placed in a container. The water content is kept constant and the rate at which water moves through the soil is measured. This is repeated for different values of θ (that is different saturation levels). It must be recommended that both K and ψ vary with θ and by its very nature, unsaturated flow involves many changes in volumetric moisture content as waves of infiltration pass.

The movement of a continuous stream of water infiltrating from the ground into the unsaturated soil may be typically seem to be as shown in F

FIGURE 7. Variation of soil moisture for water infiltrating from surface

- (a) Initial condition, water is yet to be applied
- (b) Soon after water has been applied by ponding
- (c) Some time after ponding

If the source of the water is now out off, then the distribution of water content with depth may look like as shown in Fig

SATURATED
SOIL

(B1 (b1 (C1

FIGURE 8. Variation in soil water content after the ponded water is exhausted

- (a) Soon after
- (b) Some time after
- (c) A long time after

2.5.4 Movement of water in saturated zone

The water that infiltrates through the unsaturated soil layers and move vertically ultimately reaches the saturated zone and raises the water table. Since it increases the quantity of in the saturated zone, it is also termed as 'recharge' of the ground water.

FIGURE 9. Variation of ground water table: (a) Before infiltration;
(b) During lsoon alter infiltration

Version 2 CE HT, Kharagpur

It may be observed from Figure 9 that both before any infiltration took place, there existed a gradient of the water table which showed a small gradient towards the river. However, the rise of the water table after the recharge due to infiltrating water is not uniform and thus the gradient of the water table after recharge is more than that before recharge. This has a direct bearing on the amount of ground water flow, which is proportional to the gradient. Based on actual observation or on mathematical analyses, we may draw lines of equal hydraulic head (the equipotentials) within the saturated zone, as shown in Figure 10. We may also draw the flow lines, which would be perpendicular to the equipotential lines. The flow lines, indicating the general direction of flow within the saturated soil zone is also drawn in the figure.

FLOWLINES
& EQUIPOTENTIAL
LINES

FIGURE 10. Equipotential lines and Flow lines of ground water movement:
(a) Before infiltration, with a low water table
(b) During I' soon after infiltration, with a raised water table

The rate of movement of the ground water, of course, varies with the material through which it is flowing since actually the flow is taking place through the voids which is different for different materials. The term hydraulic conductivity of a porous medium is used to indicate the ease with which water can flow through it. It is defined as the discharge taking place through a flow tube (which may be thought of as a short pipe

along a flow line) per unit area of the tube under the influence of unit hydraulic gradient (which is the difference of potential heads in unit distance along the flow line). Hydraulic conductivity is generally denoted by 'K' and if the porous material is homogeneous, then K is also likely to be the same in any direction. However, in nature, the soil layers are often formed in layers resulting in the hydraulic conductivity varying between different directions. Even porous bed rock, which is usually fractured rock, may not be fractured to the same extent in all directions. As a result, in many natural flows the flow is more in some preferential direction. This type of conducting media is referred to as being heterogeneous and the corresponding hydraulic conductivity is said to be anisotropic. In any such body. Here we qualitatively discuss the flow of ground water through a few examples which show the relative interaction between the flow and the geological properties of the porous medium. Here, the two - dimensional plane is assumed to be vertical

2.5.6 Water table contours and regional flow

For a region, like a watershed, if we plot (in a horizontal plane) contours of equal hydraulic head of the ground water, then we can analyse the movement of ground water in a regional scale.

GROUND WATER CONTOURS

FLOW LINES

:TRACE OF RIVERS

2.5.7 Aquifer properties and ground water flow

Porosity

Ground water is stored only within the pore spaces of soils or in the joints and fractures of rock which act as aquifers. The porosity of an earth material is the percentage of the rock or soil that is void of material. It is defined mathematically by the equation

$$n = \frac{100v_v}{V}$$

(2)

Where n is the porosity, expressed as percentage; v_v , is the volume of void space in a unit volume of earth material; and V is the unit volume of earth material, including both voids and solid.

Specific Yield

While porosity is a measure of the water bearing capacity of the formation, all this water cannot be drained by gravity or by pumping from wells, as a portion of the water is held in the void spaces by molecular and surface tension forces. If gravity exerts a stress on a film of water surrounding a mineral grain (forming the soil), some of the film will pull away and drip downward. The remaining film will be thinner, with a greater surface tension so that, eventually, the stress of gravity will be exactly balanced by the

surface

tension (Hygroscopic water is the moisture clinging to the soil particles because of surface tension). Considering the above phenomena, the Specific Yield (S_y) is the ratio of the volume of water that drains from a saturated soil or rock owing to the attraction of gravity to the total volume of the aquifer.

If two samples are equivalent with regard to porosity, but the average grain size of one is much smaller than the other, the surface area of the finer sample will be larger. As a result, more water can be held as hygroscopic moisture by the finer grains.

The volume of water retained by molecular and surface tension forces, against the force of gravity, expressed as a percentage of the volume of the saturated sample of the aquifer, is called Specific Retention S_r , and corresponds to what is called the Field Capacity.

Hence, the following relation holds good:

$$n = S_y + S_r \quad (3)$$

Specific storage (s_s)

Specific storage (s_s), also sometimes called the Elastic Storage Coefficient, is the amount of water per unit volume of a saturated formation that is stored or expelled from storage owing to compressibility of the mineral skeleton and the pore water per unit change in potentiometric head. Specific Storage is given by the expression

$$S_s = \alpha_w n + \beta \quad (4)$$

where α_w is the unit weight of water, or is the compressibility of the aquifer skeleton; n is the porosity; β is the compressibility of water.

Specific storage has the dimensions of length²

The storativity (S) of a confined aquifer is the product of the specific storage (s_s) and the aquifer thickness (b).

$$S = s_s b \quad (5)$$

All of the water released is accounted for by the compressibility of the mineral skeleton and pore water. The water comes from the entire thickness of the aquifer.

In an unconfined aquifer, the level of saturation rises or falls with changes in the amount of water in storage. As water level falls, water drains out from the pore spaces. This storage or release due to the specific yield (S_y) of the aquifer. For an unconfined aquifer, therefore, the storativity is found by the formula.

$$S = S_y + h S_r \quad (6)$$

Where h is the thickness of the saturated zone.

Since the value of S_r is several orders of magnitude greater than $h S_r$, for an unconfined aquifer, the storativity is usually taken to be equal to the specific yield.

2.5.8 Aquifers and confining layers

It is natural to find the natural geologic formation of a region with varying degrees of hydraulic conductivities. The permeable materials have resulted usually due to weathering, fracturing and solution effects from the parent bed rock. Hence, the

physical size of the soil grains or the pore sizes of fractured rock affect the movement of ground water flow to a great degree. Based on these, certain terms that have been used frequently in studying hydrogeology, are discussed here.

o Aquifer: This is a geologic unit that can store and transmit water at rates fast enough to supply reasonable amount to wells.

o Confining layers: This is a geologic unit having very little hydraulic conductivity. Confining layers are further subdivided as follows:

o Aquifuge: an absolutely impermeable layer that will not transmit any water.

o Aquitard: A layer of low permeability that can store ground water and also transmit slowly from one aquifer to another. Also termed as "leaky aquifer".

o Aquiclude: A unit of low permeability, but is located so that it forms an upper or lower boundary to a ground water flow system.

Aquifers which occur below land surface extending up to a depth are known as unconfined. Some aquifers are located much below the land surface, overlain by a confining layer. Such aquifers are called confined or artesian aquifers. In these aquifers, the water is under pressure and there is no free water surface like the water table of unconfined aquifer.